

RECESSED ROUND

3G-RC150-4RD
1 LIGHT LED
50MM - WITH TRIM



3G
LIGHTING



Trimless



Recessed Madison



Continuous Slots



Pendant Informa

FEATURES

CONSTRUCTION

- Housing fabricated in cold rolled steel. Black powder coated finish
- Features a 3/4" removable trim assembly
- Maximum ceiling thickness of 1". Consult factory for modifications
- Solid aluminum double gimbals. Adjustable and lockable
- Anodized aluminum reflectors and extruded aluminum heatsinks

ELECTRICAL

- Standard 120-277V, 0-10V dimmable drivers with 100-1% dimming range
- 85% efficiency and 0.9 power factor
- Lutron and eldoLED driver options available with 100-1% dimming range
- Fixture is pre-wired, thermally protected, and rated for through branch wiring
- Electrical enclosures easily accessible through fixture aperture

LED SYSTEM

- Available in 27K, 30K, 35K, and 40K
- Average rated life of > 50,000 hours
- Color consistency < 2 SDCM
- Standard (80+CRI). Optional (90+ and 97+CRI)
- LED modules carry a 5-year warranty
- Modules are field replaceable

LUMEN MAINTENANCE

- L70 at 60,000 hours

MOUNTING

- New construction housing suitable for drywall, wood, acoustic and metal pan ceilings
- Butterfly brackets compatible with 1/2" x 1/2" channel, 1/2", 5/8", 3/4" bar hangers, 1/2" EMT, and furring strips (supplied by others)

LABELS

- ETL listed. Suitable for dry or damp locations

WARRANTY




- 5 Year limited warranty

PROJECT

TYPE

DATE

CATALOG #



ORDERING INFORMATION

CAT. NO	LUMEN OUTPUT	CRI	COLOR TEMP	BEAM ANGLE	VOLTAGE
3G-RC150-4RD	10 - 1000 LUMENS	S80 - 80+CRI (STANDARD)	27K - 2700K	20D - 20°	120 - 120V
	15 - 1500 LUMENS	H90 - 90+ CRI	30K - 3000K	40D - 40°	277 - 277V
		H97 - 97+ CRI	35K - 3500K	60D - 60°	347 - 347V (0-10V ONLY)
			40K - 4000K		

3G-RC150-4RD					
---------------------	--	--	--	--	--

DRIVER	TRIM FINISH	GIMBAL FINISH	HOUSING INTERIOR	OPTIONS
DIM - 0-10V (STANDARD 100%-1) DHL2 - LUTRON (ECO SYSTEM 100-1%) DALI - DALI (100-1%) LE10 - FORWARD PHASE (100-10%) LE - FORWARD PHASE (100-1%)	WT - WHITE TRIM (STANDARD) ST - SILVER TRIM BT - BLACK TRIM	NG - NATURAL ALUMINUM (STANDARD) BG - BLACK WG - WHITE	BK - BLACK	CP - CHICAGO PLENUM BH - BAR HANGERS SF16 - SOFTENING LENS LS16 - LINEAR SPREAD HXB16 - BLACK HEXELL LOUVER
Maximum 2 optical accessories. See optical accessories page for more options				

			BK	
--	--	--	-----------	--

ORDERING EXAMPLE: **3G-RC150-4RD-15-S80-30K-40D-120-DIM-WT-NG-BK**

Copyright 2016 3G Lighting.
 P: 905-850-2305 F: 905-851-6490 | TF: 888-448-0440
 3G reserves the right to change, without notice, specifications or materials for product improvement.



RECESSED ROUND

3G-RC150-4RD
1 LIGHT LED
50MM - WITH TRIM




PERFORMANCE CHARTS

80+ CRI (Based on 40° Beam Angle)				90+ CRI (Based on 40° Beam Angle)				97+ CRI (Based on 40° Beam Angle)			
LUMEN OUTPUT	SYSTEM WATTS	DELIVERED LUMENS	EFFICACY LM/W	LUMEN OUTPUT	SYSTEM WATTS	DELIVERED LUMENS	EFFICACY LM/W	LUMEN OUTPUT	SYSTEM WATTS	DELIVERED LUMENS	EFFICACY LM/W
1000 LUMENS	9.8W	1066	109	1000 LUMENS	9.8 W	913	93	1000 LUMENS	9.8W	802	82
1500 LUMENS	13.7W	1493	109	1500 LUMENS	15.6W	1461	93	1500 LUMENS	15.6W	1282	82

P E N D I N G

MOUNTING



NOTES