



3G-SRU24
 24" RUBO
 SURFACE MOUNTED



Featuring a white sandblasted acrylic diffuser
 Proprietary LED source fully saturates the hand fabricated acrylic
 Evenly illuminated sides with distinctive lines
 Standard and high lumen output options
 Suitable for ceiling or wall applications
 1% dimming standard with several integral driver options

ORDERING INFORMATION

PROJECT:	<input type="text"/>	TYPE:	<input type="text"/>
CATALOG #:	<input type="text"/>	DATE:	<input type="text"/>

CAT. NO	LED SYSTEM	COLOR TEMP	VOLTAGE	DRIVER	FINISH	OPTIONS
3G-SRU24	L2 - STANDARD OUTPUT	27K - 2700K	UNV - 120V-277V	DIM - 0-10V (STANDARD 100-1%)	WH - WHITE (STANDARD) SV - SILVER	EM - INTEGRAL EMERGENCY BATTERY
	L4 - HIGH OUTPUT	30K - 3000K 35K - 3500K 40K - 4000K	120 - 120V 347 - 347V (0-10V ONLY)	DHL2 - LUTRON (ECO SYSTEM "H" 100-1%) DALI - DALI (100-1%) D01 - 0-10V (100-0.1%) DMX - DMX (100-0%)		
	CONSULT 3G FOR CUSTOM OUTPUTS					

PERFORMANCE CHART (Based on 3500K)

LED SYSTEM	SYSTEM WATTS	DELIVERED LUMENS	EFFICACY (LM/W)
L2 - STANDARD OUTPUT	29W	2915	101
L4 - HIGH OUTPUT	46W	4702	102

EDITION 01/19





3G-SRU24

24" RUBO - SURFACE MOUNTED

TECHNICAL

HOUSING

- White, fabricated sandblasted acrylic diffuser with distinctive lines
- Fixture collar made from spun aluminum with powder coated finish
- Reflector fabricated in steel with high reflectance white powder coated finish
- Twist and lock construction with no visible hardware
- Standard polyester powder coated matte white finish. Optional matte silver finish

ELECTRICAL

- Standard 0-10V, 100-1% dimming and 0.9 power factor
- Lutron EcoSystem and eldoLED Dali options available with 100-1% dimming
- All drivers are integral and easily accessible within fixture collar
- Integral Emergency Battery: 90 minutes

LED SYSTEM

- Proprietary LED system
- Color consistency < 3 SDCM
- Standard (80+CRI)
- Available in 27K, 30K, 35K, and 40K
- Average rated life of > 50,000 hours
- 5-year warranty

MOUNTING

- Suitable for various ceiling applications (see mounting details)
- Twist and lock mounting system with no visible hardware

LISTING

- ETL listed and tested to UL standards. Suitable for dry or damp locations

WARRANTY



- 5 Year warranty on LED and drivers
- Manufacturer 1-year warranty for defects in material and workmanship under normal use
- Ambient temperature at fixture should not exceed 25°C

3G

3G-SRU24

LIGHTING 24" RUBO - SURFACE MOUNTED

DRAWINGS AND DIMENSIONS



MOUNTING

