

STYLOS 3021


PROJECT PROJET

SPEC TYPE

NOTES



3021



ORDERING SPECIFICATION SPÉCIFICATION DE COMMANDE

CODE


MODEL MODÈLE

3021 STYLOS

3021

LIGHT SOURCE SOURCE LUMINEUSE

(WATTAGE, LAMP TYPE, LAMP FORM, BASE TYPE, OTHER INFO)

2XCF.L.18  18W X 2, CFL, LONG TWIN TUBE T5, 2G11 BASE (9" MAX LAMP)

2XCF.D.13  13W X 2, CFL, DOUBLE TWIN TUBE, G24Q1 BASE

2XCF.D.26  26W X 2, CFL, DOUBLE TWIN TUBE, G24Q3 BASE

VOLTAGE VOLTAGE

120V 120 VOLT

277V 277 VOLT

347V* 347 VOLT

*ONLY AVAILABLE WITH 2XCF.D.13 & 2XCF.D.26 (NON-DIMMING BALLAST)

DIMMING OPTION OPTION DE GRADATION

AVAILABLE WITH 2XCF.D26 ONLY

DED LUTRON ECOSYSTEM ELECTRONIC DIMMING BALLAST (ECOSYSTEM DIGITAL LINK WIRING)

DE3 LUTRON ECOSYSTEM ELECTRONIC DIMMING BALLAST (3-WIRE WIRING)

EMERGENCY BATTERY BATTERIE D'URGENCE

AVAILABLE WITH 2XCF.L.18, 2XCF.D.13 AND 2XCF.D.26, 120V OR 277V ONLY

NOT AVAILABLE WITH A DIMMING BALLAST

REM⁽¹⁾ REMOTE EMERGENCY BATTERY

⁽¹⁾ 3981 ACCESSORY IS REQUIRED FOR THIS OPTION

STRUCTURE FINISH FINI STRUCTURE

CHR CHROME

SC* SATIN CHROME

WH* WHITE

*LONGER LEAD TIME

DIFFUSER FINISH FINI DIFFUSEUR

WH WHITE

WH

ACCESSORY ACCESSOIRE

3981 JUNCTION BOX FOR CFL REMOTE EMERGENCY BATTERY

PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT



DESIGN:

Simplicity defined, elegantly arcing shade supported by two small tabs. ADA compliant.

LIGHT SOURCE:

Wide range of energy saving and dimmable light sources available.

Remote EM also available.

STRUCTURE:

Die-stamped steel structure with plated finish.

DIFFUSER:

Formed white silk-screen crystal glass.

CERTIFIED:

c-CSA-us

CONCEPTION:

La simplicité est définie par l'élégante forme courbée supportée par deux onglets.

Conforme à la norme ADA.

SOURCE LUMINEUSE:

Plusieurs sources à faible consommation et ballasts à gradation offerts.

Batterie d'urgence à distance aussi offerte.

STRUCTURE:

Acier embouti plaqué.

DIFFUSEUR:

Verre cristal formé sérigraphié blanc.

CERTIFIÉ:

c-CSA-us