

LIFT 3240


PROJECT PROJET

SPEC TYPE

NOTES



3240



ORDERING SPECIFICATION SPÉCIFICATION DE COMMANDE

CODE

MODEL MODÈLE

3240

3240 LIFT

LIGHT SOURCE SOURCE LUMINEUSE

(WATTAGE, LAMP TYPE, LAMP FORM, BASE TYPE, OTHER INFO)

CF.T.32  26/32W, CFL, DOUBLE / TRIPLE TWIN TUBE, G24Q3 BASE

CF.SP.26  26W, CFL, SPIRAL TUBE, GU24 BASE (120V ONLY)

VOLTAGE VOLTAGE

120V 120 VOLT

277V 277 VOLT

347V* 347 VOLT

*ONLY AVAILABLE WITH CF.T.32 (NON-DIMMING BALLAST)

DIMMING OPTION OPTION DE GRADATION

AVAILABLE WITH CF.T.32 ONLY

DM1 ADVANCE MARK 10 ELECTRONIC DIMMING BALLAST

DM7 ADVANCE MARK 7 ELECTRONIC DIMMING BALLAST

DED LUTRON ECOSYSTEM ELECTRONIC DIMMING BALLAST (ECOSYSTEM DIGITAL LINK WIRING)

DE3 LUTRON ECOSYSTEM ELECTRONIC DIMMING BALLAST (3-WIRE WIRING)

EMERGENCY BATTERY BATTERIE D'URGENCE

AVAILABLE WITH CF.T.32, 120V OR 277V ONLY

NOT AVAILABLE WITH A DIMMING BALLAST

REM ⁽¹⁾ RECESSED EMERGENCY BATTERY*

⁽¹⁾ 3981 ACCESSORY IS REQUIRED FOR THIS OPTION

STRUCTURE FINISH FINI STRUCTURE

SA SATIN ALUMINUM

WH WHITE

REFLECTOR FINISH FINI RÉFLECTEUR

WH

WH WHITE

ACCESSORY ACCESSOIRE

3981 JUNCTION BOX FOR CFL REMOTE EMERGENCY BATTERY

PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT



DESIGN:

Classic cylindrical form with a parabolic reflector can be rotated to spread light outwards from its top.

INSTALLATION:

Vertical mounting is recommended.

LIGHT SOURCE:

Standard or dimmable fluorescent light sources available.

STRUCTURE:

Machined aluminum body with steel inner structure.

REFLECTOR:

Parabolic die-formed aluminum with highly reflective white polyester powder paint.

CERTIFIED:

c-CSA-us

CONCEPTION:

Forme cylindrique avec un réflecteur parabolique ajustable pour éclairer vers le haut.

INSTALLATION:

Position verticale recommandée.

SOURCE LUMINEUSE:

Fluorescents avec ou sans option de gradation disponibles.

STRUCTURE:

Aluminium usiné avec structure interne en acier.

RÉFLECTEUR:

Aluminium embouti avec peinture électrostatique blanche à base de polyester très réfléchissante.

CERTIFIÉ:

c-CSA-us