



corrugated
regressed trim




solid
regressed trim



flush lens

DIMENSIONAL DATA



FEATURES

Narrow 3" slot LED with frosted satin lens.


Shielding options include corrugated or solid regressed trim or flush lens.

Avenue B LED allows ceiling tiles to rest on fixture rails, keeping ceilings clean without the need for additional tees.

Drywall installation available.

Avenue[®] B LED is a great solution for general illumination in a narrow aperture.

PERFORMANCE



PRODUCT OVERVIEW

Lumen Output:	1759-3217lm
Wattage:	22-38W
LPW:	73-92
SDCM:	3

Standard Output (LL1)
4' Housing with Flush Lens

Delivered Lumens: 2034lm


Total System Watts: 22W

Visit focalpointlights.com for complete photometric data.

fixture:

project:

MOUNTING INFORMATION



SPECIFICATIONS

LED System

Proprietary linear LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. LEDs are placed to promote a uniform appearance. Available in 3000K, 3500K or 4000K with CRI>80, 3SDCM. LED modules and drivers are replaceable from below.

Construction

One-piece 20 Ga. steel housing. Thermally protected housing for new construction applications without direct contact with insulation. Insulation to be kept 3" away from housing. Corrugated and solid regressed trim constructed of extruded aluminum finished in Matte Satin White. Grid luminaires include 20 Ga. steel, .5" wide flange rail finished in Matte Satin White. Drywall flange option is provided with 20 Ga. steel, .5" wide flange kit and 20 Ga. galvanized steel mounting yoke. 2' unit weight: 5 lbs., 4' unit weight: 7 lbs.

Optic

22 Ga. steel reflectors finished in High Reflectance White powder coat. Frosted Acrylic lens diffuser .118" thick.

Electrical

Thru-wiring not available. Voltage specific thermal protectors included standard.

Emergency Battery

Bodine BSL310-CAN. Emergency output - 10 watts for 90 minutes. Maximum mounting height: 20ft.

Labels

UL and cUL Listed. Suitable for Dry or Damp Locations, indoor use only.

Finish

Polyester powder coat applied over a multi-stage pre-treatment.

Lumen Maintenance

Reported: L70 at >60,000 hours Calculated: L70 at 84,000 hours
Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.

Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

Warranty

LED system rated for operation in ambient environments up to 25°C. 5-year limited warranty.

4' PERFORMANCE CHART

Shielding	LED System	Tested System		
		Delivered Lumens	Watts	LPW
SR	Standard output	1759	22	80
	Medium output	2164	27	80
	High output	2769	38	73
FL	Standard output	2034	22	92
	Medium output	2425	27	90
	High output	3217	38	85

Based on 3500K. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%

Focal Point LLC reserves the right to change specifications for product improvement without notification.

ORDERING

Luminaire Series	FAVBL
Avenue B LED	FAVBL
Shielding	
Corrugated Regressed Trim Frst.Lns	CR
Solid Regressed Trim Frosted Lens	SR
Flush Frosted Lens	FL
LED System	
Standard Output	LL1
Medium Output	LL2
High Output	LL3
Color Temperature	
3000K	30K
3500K	35K
4000K	40K
Circuits	
Single Circuit	1C
Voltage	
120 Volt	120
277 Volt	277
Control System & Dimming Level	
0-10V - 10% Dimming	LD1
Step Dimming	SD5
Lutron H-Series - 1% Dimming (LL3 Output, 4' housing only)	LH1
Lutron 5-Series - 5% EcoSystem Digital (LL3 Output, 4' housing only)	LU5
Ceiling Configurations	
Drywall Flange	F
Std. 15/16" Lay-in	G1
Std. 15/16" Tegular	T1
Std. 15/16" Tegular, against Tee	T1T
Std. 9/16" Lay-in	G2
Std. 9/16" Tegular	T2
Std. 9/16" Tegular, against Tee	T2T
9/16" Slot-tee Tegular	G3
Tall 15/16" Lay-in	G4
Tall 15/16" Tegular	T4
Tall 15/16" Tegular, against Tee	T4T
Tall 9/16" Lay-in	G5
Tall 9/16" Tegular	T5
Tall 9/16" Tegular, against Tee	T5T
Node 9/16" Tegular	T6
Node 9/16" Tegular, against Tee	T6T
<small>(For TechZone™ compatible luminaires see Avenue B TechZone)</small>	
Factory Options	
Chicago Plenum	CP
Emergency Battery Pack <small>(Not available in 2' housing)</small>	EM
Positional Clips	EQ
6' New York City Flex Whip	FNY
6' Flex Whip	FW
Finish	
Matte White Housing	WH
Luminaire Length	
4' Nominal Housing	4'
8' Nominal Housing	8'



Options in orange qualify for the Quickship program. 10-day up to 100 pieces. Refer to Quickship Guide for complete details.

For more information visit focalpointlights.com/reference or consult factory.