

ID+ 2.5" x 2.5"

LED WALL WASH



FOCAL POINT®




clear diffuse reflector



matte black reflector



warm diffuse reflector



white trim



titanium silver trim




bronze trim



black trim

DIMENSIONAL DATA



FEATURES


Small aperture LED 30° fixed wall wash.

Selection of dimming drivers available.


Selection of trim styles and finishes to complement any design.

Adjustable accent & downlight also available.

PERFORMANCE



HOUSING DETAILS



HOUSING SPECIFICATIONS

Construction

Die-formed housing and integral junction box with (7) 1/2" pry outs. Accommodates ceiling thicknesses up to 1". For thicker ceiling consult factory. Die-cast aluminum heat sink designed for maximum thermal dissipation. Fixture will not exceed 5 lb.

(T) Thermally protected housing for new construction. Insulation to be kept 3" away from housing. Butterfly brackets allow mounting to 1/2" emt. Order bar hangers as an accessory.

Electrical

Choice of constant current dimming drivers. Power factor >.9 typical, 50/60 Hz., 350-2080mA.

Emergency battery

Bodine BSL17C-C2. Emergency output—7 watts for 90 minutes.

Labels

UL and cUL listed. Suitable for Dry or Damp Locations, indoor use only.

Lumen Maintenance

Reported: L70 at >36,000 hours
Derived from EPA TM-21 calculator.

Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

Warranty

LED System rated for operation in ambient environments up to 25°C. 5-year limited warranty.

TRIM SPECIFICATIONS

LED System

Proprietary LED module with color accuracy within 2 SDCM.

Aesthetics

Parabolic reflector cone ensures glare free optics. Field-paintable flange. Trim clips pull trim tight to the ceiling.

Optics

Beamspread achieved with optical filters.

PERFORMANCE CHART

Lumen Ouput	Distribution	System Watts
500	NFL	14

*Tested with 3500K Clear Diffuse Reflector. **Lumen output may vary +/- 5%. 0.963 Matte Black Reflector (BK) lumen multiplier.

HOUSING ORDERING

Housing Series	ID+ 2.5" Square Housing	FLS22	FLS22W
Trim Type	Square Flush	SF	
	Square Overlap	SO	
Lumen Ouput	500 Lumens	500L	500L
Voltage	120V	120	
	277V	277	
Driver	0-10V - 1% Dimming	L11	
	0-10V - 10% Dimming	LD1	
	Lutron H-Series - 1% Dimming	LH1	
	Lutron 5-Series -		
	5% EcoSystem Digital	LU5	
	DALI - 1% Dimming	D11	
	Lutron A-Series - Forward Phase	LTE	
	(120 only)		
Housing Type	Thermally Protected, Non-IC	T	T
Factory Options	Bar Hangers	BH	
	Emergency Battery Pack	EM	
	(Remote test switch, above ceiling access, SO trim only)		
TRIM & LED MODULE			
Aperture	2.5" Square Aperture	LS22	LS22
Trim Type	Square	SQ	SQ
Color Temperature	2700K, 90+ CRI	927K	
	3000K, 90+ CRI	930K	
	3000K, 80+ CRI	30K	
	3500K, 80+ CRI	35K	
Optic	Wall Wash	WW	WW
Distribution	20° Narrow Flood	NFL	NFL
Reflector Color	Clear Diffuse	CD	
	Matte Black	BK	
	Warm Diffuse	WD	
Flange Finish	White	WH	
	Black	BK	
	Titanium Silver	TS	
	Bronze	BR	